

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page1 of 17  
Print date: 17-2-2025

## **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

### **1.1 Product identification:**

Product name: Silicone ASSYST W22 - rapid hardener  
UFI code: UVD9-614T-Y228-Y49C

### **1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Usage: Hardener. Catalyst.  
Uses advised against: Not suitable for DIY.

### **1.3 Details of the supplier of the safety data sheet:**

Responsible distributor : ASSYST bvba / A.S.O.W. bvba  
Hellegatstraat 13a  
2590 Berlaar  
Belgium  
Tel: +32 495 50 61 14 / +32 496 83 70 27  
Website: [www.assyst.org](http://www.assyst.org) / [www.artsuppliesonweb.com](http://www.artsuppliesonweb.com)  
Email: [ao@assyst.org](mailto:ao@assyst.org) / [vera.opsommer@assyst.org](mailto:vera.opsommer@assyst.org)

### **1.4 Emergency phone number:**

For Belgium:

Call the **Poison Control Centre (070 245 245 - free)**, if not available: **02 264 96 30** (normal rate) or your doctor. In life-threatening situations, always call the European emergency number **112**.

NHS 24 Direct

For help from a GP, visit your GP surgery's website, use an online service to contact your GP, or call the surgery. **For urgent medical help**, use the NHS 111 online service, or **call 111** if you are unable to get help online. **For life-threatening emergencies, call 999** for an ambulance. There is more information about getting medical help on the NHS website.

## **SECTION 2: Hazard identification**

### **2.1 Classification of the substance or mixture:**

**Classification according to directive (EC) No 1272/2008 and its amendments.**

The product is classified according to current legislation.

**Classification in accordance with Regulation (EC) No 1272/2008 as amended.**

#### **Health hazards**

Flammable liquids, category 3 - H226 Flammable liquid and vapour.

Serious eye damage/eye irritation, category 2 - H319 Causes severe eye irritation.

Acute toxicity, by inhalation, category 4 - H332 Harmful by inhalation.

Specific target organ toxicity, single exposure; respiratory tract irritation, category 3 - H335 May cause respiratory tract irritation.

### **2.2 Labelling elements:**

**Labelling according to regulation (EC) No 1272/2008 [CLP/GHS]:**



**Hazard pictograms:**

**Signal word**

Warning.

**Hazard-determining components for labelling:**

- ✓ Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

**Hazard statements:**

H226 Flammable liquid and vapour

H319 Causes severe eye irritation.

H332 Harmful by inhalation.

# SAFETY DATA SHEET

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page2 of 17  
Print date: 17-2-2025

H335 May cause respiratory tract irritation.

## Precautions

### Prevention:

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P233 Keep in tightly closed container.
- P240 Ground storage and collection container.
- P241 Use explosion-proof electrical/ventilation/lighting/...equipment.
- P242 Only use spark-free tools.
- P243 Take precautions against static discharges.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Action:

- P303+361+353 IF ON SKIN (or hair): remove contaminated clothing immediately - rinse skin with water/shower.
- P370+378 In case of fire: extinguish with dry powder, CO2.
- P403+235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local and national regulations.

### Additional hazard statements:

No

For use by professionals only.

### 2.3 Other hazards:

This substance/mixture does not contain any components that can be considered persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Ecological information

The substance/mixture does not contain any components believed to have endocrine-disrupting properties according to REACH article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at level 0.1% or higher.

### Toxicological information:

The substance/mixture does not contain any components believed to have endocrine-disrupting properties according to REACH article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at level 0.1% or higher.

## SECTION 3: Composition and information on ingredients

### 3.2 Mixtures:

Description

Chemical name	CAS no. EC no. Index no. REACH registration number	CLP classification	Conc.
Siloxanes and Silicones, di-Me	63148-62-9 613-156-5 - -	-	66,5%
Tetraethyl silicate	78-10-4 201-083-8 014-005-00-0 01-2119496195-28	Flam. Liq. 3, H226; Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335  <u>Acute toxicity estimates</u> <b>Acute oral toxicity:</b> > 2 500 mg/kg <b>Acute toxicity by inhalation:</b> > 16.8 mg/l, 4 h, dust/mist 10 mg/l, 4 h, dust/mist 17 mg/l, 4 h, vapours <b>Acute dermal toxicity:</b> 5 878 mg/kg	30%
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	68928-76-7	Acute Tox. 4; H302	3%

# SAFETY DATA SHEET

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page3 of 17  
Print date: 17-2-2025

	273-028-6 - 01-2120770324-57	Skin Irrit. 2; H315 Skin Sens. 1A; H317 Aquatic Chronic 3; H412  <u>Acute toxicity estimates</u> <b>Acute oral toxicity:</b> 892 mg/kg <b>Acute dermal toxicity:</b> > 2 000 mg/kg	
Titanium tetrabutanolate	5593-70-4 227-006-8 - -	Flam. Liq. 3 ; H226 Skin Irrit. 2 ; H315 Eye Dam. 1 ; H318 STOT SE 3 ; H335 (inhalation) STOT SE 3 ; H336 (inhalation, oral)	0.5%

\* All concentrations are expressed by weight unless the component is a gas.

Gas concentrations are expressed as volume percentages.

Full text of H-phrases in section 16.

## **SECTION 4: First aid measures**

### **4.1 Description of first-aid measures:**

#### **General advice:**

First aiders should take care of self-protection and use the recommended protective clothing (chemical-resistant gloves, splash protection).

If there is an exposure risk, refer to section 8 for specific personal protective equipment.

#### **Inhalation:**

Bring the person into fresh air and let them breathe comfortably.

Breathe artificially if not breathing; if mouth-to-mouth, use protection (pocket face mask, etc.).

Oxygen should be given by qualified personnel if breathing is difficult.

Contact a doctor or transport it to a medical facility.

#### **Skin touch:**

Remove the material from the skin immediately by washing with soap and plenty of water.

Remove contaminated clothing and shoes during washing.

Consult a doctor if irritation or rash occurs.

Wash clothes for reuse.

Remove all accessories that cannot be disinfected, including leather goods such as shoes, belts and watch straps.

An appropriate emergency safety shower facility should be available at the workplace.

#### **Eye contact:**

Rinse eyes thoroughly with water for several minutes.

Remove contact lenses after the first 1-2 minutes and continue rinsing for several minutes.

Consult a doctor if adverse reactions occur, preferably an ophthalmologist. An appropriate emergency eye wash facility should be available in the work area.

#### **Ingestion:**

In case of ingestion, consult a doctor.

Do not induce vomiting unless ordered by medical staff.

### **4.2 Main acute and delayed symptoms and effects:**

Causes skin irritation.

May cause allergic skin reaction.

### **4.3 Indication of immediate medical attention and special treatment required:**

#### **Notes for the doctor:**

No specific antidote.

Treatment of exposure should take into account the patient's symptoms and clinical condition.

Skin contact may worsen an existing dermatitis.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page4 of 17  
Print date: 17-2-2025

## **SECTION 5: Fire-fighting measures**

### **5.1 Extinguishing media:**

#### **Suitable extinguishing agents:**

Alcohol-resistant foam.

Carbon dioxide (CO<sub>2</sub>).

Drying powder.

Dry sand.

#### **Extinguishing agents not suitable from a safety point of view:**

Strong water jet.

Do not use a direct water jet.

### **5.2 Special hazards arising from the substance or mixture:**

#### **Hazardous combustion products:**

Carbon oxides. Silicon oxide. Nitrogen oxides (NO<sub>x</sub>). Oxides of phosphorus. Metal oxides.

#### **Unusual fire and explosion hazards:**

Fire recoil possible over a considerable distance.

Exposure to combination products can be hazardous to health.

At temperatures above the flash point, flammable vapour concentrations may accumulate; see Sec. 9.

Combustible mixtures may occur in the vapour space of the container at room temperature.

Closed vessels can rupture due to pressure build-up when exposed to fire or extreme heat.

Vapours can form explosive mixtures with air.

### **5.3 Advice for firefighters:**

#### **Fire-fighting measures:**

Use water spray to cool unopened containers.

Evacuate.

Collect contaminated firefighting water separately.

It should not drain to the sewerage system.

Combustion residues and contaminated fire fighting water must be disposed of according to local regulations.

If possible, prevent the run-off of extinguishing water.

Extinguishing water, which has run off, can cause damage to the environment.

Use water spray to cool vessels exposed to fire and the area involved in the fire until the fire is extinguished and the danger of re-ignition has passed.

Do not use a steady stream of water as it may splatter and spread the fire.

Use extinguishing agents suitable for the local conditions and environment.

Remove undamaged holder from fire area if it is safe to do so.

#### **Special protective equipment for firefighters:**

In case of fire, wear a compressed air mask.

Use personal protective equipment.

## **SECTION 6: Measures in case of accidental release of the substance or mixture**

### **6.1 Personal precautions, protective equipment and emergency procedures:**

Remove all ignition sources.

Use personal protective equipment.

Avoid all ignition sources in the vicinity of spills or released vapours to prevent fire or explosion.

Ground all containers and processing equipment.

Explosion hazard from vapours, keep away from drains.

Follow the advice on working safely with the substance and recommendations on personal protective equipment.

### **6.2 Environmental precautions:**

Do not release the product into the aquatic environment above the legal limits.

Avoid further leaks and spills if it is safe to do so.

Prevent spreading over a large area (e.g. by containment or oil baffles).

Collect and dispose of contaminated cleaning water.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page5 of 17  
Print date: 17-2-2025

In case of significant leaks that cannot be contained, the local government should be notified.

#### 6.3 Methods and materials for containment and cleaning:

Only use non-sparking tools.

Absorb in inert absorbent material.

Precipitate gases/fumes/mists using a water spray jet.

Wipe with absorbent material or pick it up and dispose of in a lidded bin.

Local or national regulations may apply both to leaks or disposal of the material, and to the materials used in cleaning operations.

You must determine which regulations apply.

To prevent material from spreading, proper barricades or other appropriate containment should be used for large spills.

If material can be pumped out, the collected material should be stored in appropriate containers.

#### 6.4 Reference to other sections:

See sections: 7, 8, 11, 12 and 13.

### **SECTION 7: Handling and storage:**

#### 7.1 Precautions for safe handling of the substance or mixture:

Do not allow to come into contact with skin or clothing.

Avoid inhalation of vapour or mist.

Avoid contact with eyes.

Do not swallow.

Keep in tightly closed container.

Keep away from heat and ignition sources.

Take measures against static electricity discharges.

Prevent leaks and spread into the environment and minimise the amount released.

Only use non-sparking tools.

Use according to common rules and practices related to industrial hygiene and safety.

EMPTY DRUMS CAN BE DANGEROUS.

Empty drums contain product residues.

Follow all product safety and label regulations, even if the vessel is empty.

Use with adequate exhaust ventilation.

Use only in an area equipped with explosion-proof extraction ventilation.

Ensure that all devices are electrically earthed prior to starting to transfer.

This material can accumulate static charge based on its inherent physical properties and can therefore be an electrical ignition source for vapours.

As earthing alone does not provide sufficient precaution against static electricity, it is necessary to introduce an inert gas into the container before starting to transfer the material.

Limit speed current to reduce accumulation of static electricity.

Ground storage and collection tank.

#### 7.2 Conditions for safe storage, including incompatibilities:

Store in correctly labelled containers.

Keep behind lock.

Store tightly closed.

Store in a cool and well-ventilated place.

Store according to relevant national regulations.

Keep away from heat and ignition sources.

Do not store with the following product types:

- ✓ Strong oxidising agents.
- ✓ Organic peroxides.
- ✓ Flammable solids.
- ✓ Pyrophoric liquids.
- ✓ Pyrophoric solids.

# SAFETY DATA SHEET

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page6 of 17  
Print date: 17-2-2025

- ✓ Substances and mixtures liable to self-heat.
- ✓ Substances and mixtures that develop flammable gases in contact with water.
- ✓ Explosives.
- ✓ Gases.

## Unsuitable materials for containers:

Nothing known.

## 7.3 Specific end use:

Refer to the technical data sheet of this product for more information.

## SECTION 8: Exposure controls/personal protection measures

### 8.1 Control parameters:

If exposure limits exist, they are listed below. If no exposure limits are shown, no values apply.

Component	Regulation	Type of statement	Value
Stannane, dimethylbis[(1-oxoneodecyl)oxy]-	ACGIH	TWA	0.1 mg/m <sup>3</sup> , Tin
	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of absorption through skin		
	ACGIH	STEL	0.2 mg/m <sup>3</sup> , Tin
	Further information: A4: Not classifiable as a human carcinogen; Skin: Danger of absorption through skin		
	BE OEL	TGG 8 hr	0.1 mg/m <sup>3</sup> , Tin
	Further information: D: Uptake of the agent through the skin, mucous membranes or eyes constitutes an important part of the total exposure. This uptake may result from both direct contact and its presence in the air.		
	BE OEL	TGG 15 min	0.2 mg/m <sup>3</sup> , Tin
	Further information: D: Uptake of the agent through the skin, mucous membranes or eyes constitutes an important part of the total exposure. This uptake may result from both direct contact and its presence in the air.		
Tetraethyl silicate	ACGIH	TWA	10 ppm
	BE OEL	TGG 8 hr	44 mg/m <sup>3</sup> 5 ppm
	2017/164/EU	TWA	44 mg/m <sup>3</sup> 5 ppm
	Further information: Indicative		

### Recommended observation procedures

Monitoring the concentration of substances in the breathing zone of workers or in the general work area may be necessary to confirm compliance with occupational exposure limits and adequacy of exposure. Biological monitoring may also be appropriate for some substances.

Validated exposure measurement methods should be applied by a competent person and samples should be analysed by an accredited laboratory.

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace exposure - Measurement of inhalation exposure to chemicals - Strategy to comply with occupational exposure limits). European Standard EN 14042 (Workplace atmospheres - Directive on the application and use of procedures for the assessment of exposure to chemical and biological agents). European Standard EN 482 (Workplace atmosphere - General requirements for the implementation of procedures for measuring chemical substances). Reference to national guidelines on methods for the determination of hazardous substances is also required.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier.

Further national methods may be available.

- ✓ National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods.
- ✓ Occupational Safety and Health Administration (OSHA), USA: sampling and analytical methods.
- ✓ Health and Safety Executive (HSE), UK: methods for determining hazardous substances.
- ✓ Institut für Arbeitsschutz Deutsche Gesetzlichen Unfallversicherung (IFA), Germany.
- ✓ L'Institut National de Recherche et de Sécurité, (INRS), France.

### Derived doses without effect

tetraethyl silicate

# SAFETY DATA SHEET

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page7 of 17  
Print date: 17-2-2025

## Employees

Acute - systemic effects		Acute - local effects		Long-term - systemic effects		Long-term - local effects	
Skin	Inhalation	Skin	Inhalation	Skin	Inhalation	Skin	Inhalation
12.1 mg/kg bw/day	85 mg/m <sup>3</sup>	n.a.	85 mg/m <sup>3</sup>	12.1 mg/kg bw/day	85 mg/m <sup>3</sup>	n.a.	85 mg/m <sup>3</sup>

## Consumers

Acute - systemic effects			Acute - local effects		Long-term - systemic effects			Long-term - local effects	
Skin	Inhalation	Oral	Skin	Inhalation	Skin	Inhalation	Oral	Skin	Inhalation
8.4 mg/kg bw/day	25 mg/m <sup>3</sup>	n.a.	n.a.	25 mg/m <sup>3</sup>	8.4 mg/kg bw/day	25 mg/m <sup>3</sup>	n.a.	n.a.	25 mg/m <sup>3</sup>

## Predicted concentration without effect

### Tetraethyl silicate

Compartment	PNEC
Freshwater	0.192 mg/l
Seawater	0.0192 mg/l
Freshwater deposition	0.18 mg/kg
Sea deposits	0.018 mg/kg
Bottom	0.05 mg/kg
Sewage treatment plant	4000 mg/l

## 8.2 Exposure control measures:

### Technical controls:

Provide local exhaust ventilation, or other technical measures to keep atmospheric concentrations below limit values.

If no limits exist, general ventilation should be sufficient for most operations.

Local extraction may be necessary for some work.

### Personal protection devices:

#### Eye/face protection:

Use safety glasses with side shields.

Safety glasses with side shields must comply with standard EN 166 or a similar standard.

If exposure causes eye irritation, use a full-face mask (complying with Standard EN 136) with a filter for organic vapours (complying with Standard EN 14387).

#### Skin protection

##### Hand protection:

Use chemical-resistant gloves classified under EN374: gloves for protection against chemicals and micro-organisms.

Examples of barrier glove materials to be preferred:

- ✓ Butyl rubber
- ✓ Natural rubber (latex).
- ✓ Neoprene.
- ✓ Nitrile/butadiene rubber ("nitrile" or "NBR").
- ✓ Ethyl vinyl alcohol laminate ("EVAL").
- ✓ Polyvinyl chloride ("PVC" or "vinyl").

When prolonged or frequently repeated contact may occur, gloves with a protection class 5 or higher (breakthrough time greater than 240 minutes according to EN 374) are recommended.

When only brief contact is expected, gloves with a protection class 3 or higher (breakthrough time greater than 60 minutes according to EN 374) are recommended.

Glove thickness alone is not a good indicator of the level of protection a glove gives against a chemical, as this level of protection is also highly dependent on the specific composition of the material the glove is made of. Depending on the material model and type, the thickness of the glove should generally be more than 0.35 mm. to provide sufficient protection in continuous and regular contact with the fabric.

As an exception to this general rule, multilayer laminate gloves are known to provide further protection at thicknesses below 0.35 mm.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page8 of 17  
Print date: 17-2-2025

Other glove materials with a thickness less than 0.35 mm. can provide sufficient protection when only brief contact is expected.

ATTENTION: The selection of specific gloves for a given application and time of use in a workplace should also take into account all other relevant factors at the workplace, such as (but not limited to): other chemicals that may be handled, physical requirements (protection against cutting/ piercing, dexterity, thermal protection), possible physical reactions to the glove material, and the instructions/specifications of the glove supplier.

#### Other protection:

Use non-permeable protective clothing that can withstand this product.

The choice of specific items such as face mask, gloves, boots, apron or full suit depends on the work.

#### Respiratory protection:

A respirator should be worn when there is a risk of exceeding exposure limits.

If no exposure limits or guidelines exist, use an approved respirator.

When respiratory protection is required, use an approved fresh air respirator (type: positive pressure) or an approved fresh air respirator (type: positive pressure) with supplemental air supply.

In an emergency, use an approved compressed air breathing apparatus (type: positive pressure).

#### Managing environmental exposure

See SECTION 7: Handling and storage and SECTION 13: Instructions for disposal measures to prevent excessive exposure to the environment during use and waste disposal.

### **SECTION 9: Physical and chemical properties**

#### **9.1 Information on basic physical and chemical properties:**

##### **Prevent**

Physical state:	liquid
Colour:	Clear to slightly cloudy, colourless
Odour:	not significant
Odour threshold:	No data available
pH:	Not applicable, substance/mixture not soluble (in water)

##### **Melting/freezing point**

Melting point/trajectory:	No data available
Freezing point:	Not implemented

##### **Boiling point or initial boiling point and boiling range**

Boiling point (760 mmHg):	> 35°C
Flash point:	Closed cup 34°C
Flammability (solid, gas):	Flammable.
Flammability (liquids):	Not performed
Lower explosion limit:	No data available
Upper explosion limit:	No data available
Vapour pressure:	No data available
Relative vapour density (air = 1):	No data available
Relative density (water = 1):	approx. 1.004
Solubility in water:	Insoluble
Partition coefficient: n-octanol/water:	Not performed
Self-ignition temperature:	No data available
Decomposition temperature:	No data available
Kinematic viscosity:	No data available

##### **Particle characteristics**

Particle size:	Not applicable
----------------	----------------

#### **9.2 Other information**

Molecular weight:	No data available
Dynamic viscosity:	No data available
Explosive properties:	Not explosive

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page9 of 17  
Print date: 17-2-2025

Oxidising properties:	The substance or mixture is not classified as oxidising.
Self-heating substances:	The substance or mixture is not classified as self-heating.
Corrosion rate of metal:	Not corrosive to metals
Evaporation rate (Butyl acetate = 1):	No data available

NOTE :The physical and chemical data shown in section 9 are typical values for this product and are not intended as product specifications.

## **SECTION 10: Stability and reactivity**

### 10.1 Reactivity:

Not classified as hazardous due to reactivity.

### 10.2 Chemical Stability:

Stable under normal conditions.

### 10.3 Potential Hazardous Reactions:

May react with strongly oxidising substances.

Vapours may form explosive mixture with air.

Flammable liquid and vapour.

### 10.4 Conditions to avoid:

Avoid static discharge.

Heat, flames and sparks.

### 10.5 Chemically interacting Materials:

Avoid contact with oxidising substances.

### 10.6 Hazardous Decomposition Products:

Decomposition products may include - among others - the following: Carbon oxide.

## **SECTION 11: Toxicological information**

Toxicological information is displayed in this section when available.

### 11.1 Information on toxicological effects:

#### **Information on likely routes of exposure**

Inhalation, Eye contact, Skin contact, Ingestion.

**Acute toxicity (represents short-term exposures with immediate effects - no chronic/delayed effects known unless otherwise stated)**

#### **Endpoints acute toxicity:**

##### **Acute oral toxicity**

Very low toxicity if swallowed.

Ingestion may cause irritation of the mouth, throat and gastrointestinal tract.

May cause nausea or vomiting.

As product. The oral LD50 of a single dose has not been determined.

Based on information for component(s):

LD50, > 5 000 mg/kg estimated

#### Information for components:

Stannane, dimethylbis[(1-oxodecyl)oxy]-

LD50, Rat, male and female, 892 mg/kg OECD 401 or equivalent

tetraethyl silicate

LD50, Rat, male and female, > 2 500 mg/kg OECD Test Guideline 425

No deaths were observed at this concentration.

Titanium tetrabutanolate

LD50, Rat, male and female, 3122 mg/kg OECD 401 or equivalent

#### **Acute dermal toxicity**

#### Information for the product:

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product. The dermal LD50 has not been determined.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page10 of 17  
Print date: 17-2-2025

Based on information for component(s):

LD50, > 2 000 mg/kg estimated

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

LD50, Rat, > 2 000 mg/kg

tetraethyl silicate

LD50, Rabbit, 5 878 mg/kg

### **Acute toxicity by inhalation**

Information for the product:

It is unlikely that short-term exposure (a few minutes) would cause adverse effects.

The vapours may cause irritation of the upper respiratory tract (nose and throat) and lungs.

Mist may cause irritation of the upper respiratory organs (nose and throat).

Overexposure can lead to Headaches.

May cause drowsiness and dizziness.

As product. The LC50 was not determined.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

As product. The LC50 was not determined.

Tetraethyl silicate

Prolonged excessive exposure can cause adverse effects.

The vapours may cause irritation of the upper respiratory tract (nose and throat) and lungs.

LC50, Rat, male, 4 h, dust/mist, 10 mg/l Guideline test OECD 403

LC50, Rat, female, 4 h, dust/mist, > 16.8 mg/l Guideline test OECD 403

### **Skin corrosion/irritation**

Causes skin irritation.

Information for the product:

Based on information for component(s):

Brief contact may cause skin irritation with local redness.

Can cause dehydration and scaling of the skin.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

Brief contact may cause skin irritation with local redness.

tetraethyl silicate

Brief contact may cause moderate skin irritation with local redness.

Can cause dehydration and scaling of the skin.

### **Serious eye damage/eye irritation**

Information for the product:

Based on information for component(s):

May cause slight eye irritation.

May cause transient, mild corneal damage.

Vapours may cause eye irritation, with mild discomfort and redness.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

May cause slight eye irritation.

May cause transient, mild corneal damage.

tetraethyl silicate

Based on product testing:

Essentially non-irritating to the eyes.

Corneal damage is unlikely.

The following symptoms may occur in humans: Vapours may cause eye irritation, with mild discomfort and redness.

### **Sensitisation**

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page11 of 17  
Print date: 17-2-2025

In case of skin hypersensitivity:

Contains one or more ingredients that caused allergic skin sensitisation in the Guinean piglet.

Respiratory sensitisation:

No relevant data found.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

Has caused allergic skin reactions in guinea pig trials.

Respiratory sensitisation:

No relevant data found.

**In case of skin hypersensitivity:**

May cause allergic skin reaction.

Information for the product:

In case of skin hypersensitivity:

Has caused allergic skin reactions in guinea pig trials.

Respiratory sensitisation:

No relevant data found.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

Has caused allergic skin reactions in guinea pig trials.

Respiratory sensitisation:

No relevant data found.

tetraethyl silicate

In case of skin hypersensitivity:

Did not cause allergic skin reactions when tested with guinea pigs.

Respiratory sensitisation:

No relevant data found.

**Specific target organ system toxicity (single exposure)**

Information for the product:

Contains components classified as toxic to specific target organs at single exposure, category 3.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

Available data are insufficient to determine an exposure-specific target organ toxicity.

tetraethyl silicate

May cause respiratory irritation.

Route of exposure: Inhalation

Target organs: respiratory system

**Inhalation hazard**

Information for the product:

Based on the physical properties, inhalation hazards are unlikely to exist.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

Based on the physical properties, inhalation hazards are unlikely to exist.

tetraethyl silicate

Based on available information, no inhalation hazard could be identified.

**Chronic toxicity (represents long-term repeated dose exposure resulting in chronic/delayed effects - no immediate effects known unless otherwise stated)**

**Specific target organ system toxicity (repeated exposure)**

Information for the product:

Contains ingredients reported to cause effects in animals on the following organs:

- ✓ Kidney.
- ✓ Blood
- ✓ Liver

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page12 of 17  
Print date: 17-2-2025

- ✓ Immunity system.

#### Information for components:

##### Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

In animals, effects to the following organs have been observed:

- ✓ Blood
- ✓ Kidney
- ✓ Liver
- ✓ Immunity system.

##### tetraethyl silicate

In animals, effects to the following organs have been observed:

- ✓ Kidney.

#### **Carcinogenicity**

##### Information for the product:

Contains component(s) that did not cause cancer in long-term studies in animals using exposure routes considered relevant for industrial handling.

##### Information for components:

##### Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

No relevant data found.

##### tetraethyl silicate

No relevant data found.

#### **Teratogenicity**

##### Information for the product:

Contains ingredients that have caused birth defects in laboratory animals.

##### Information for components:

##### Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

No relevant data found.

##### tetraethyl silicate

Did not cause birth defects or other effects to the foetus, even at doses that caused toxic effects in the mother.

#### **Reproductive toxicity**

##### Information for the product:

Contains one or more components that have impaired fertility in studies on animals.

##### Information for components:

##### Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

No relevant data found.

##### tetraethyl silicate

In animal studies, the product had no effects on reproduction. In animal studies, the product did not interfere with reproduction.

#### **Mutagenicity**

##### Information for the product:

Contains one or more components that have given negative results in some in vitro genetic toxicity studies, positive results in others.

Mutagenicity studies in animals have given negative results for the components studied.

##### Information for components:

##### Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

In vitro studies of genetic toxicity were negative in some cases and positive in others.

Genetic toxicity studies on animals were negative.

##### tetraethyl silicate

Genetic toxicity studies in vitro were predominantly negative.

#### **11.2 Information on other hazards**

#### **Endocrine-disrupting properties**

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page13 of 17  
Print date: 17-2-2025

The substance/mixture does not contain any components believed to have endocrine-disrupting properties according to REACH article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at level 0.1% or higher.

Information for components:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

This substance is not considered to have endocrine-disrupting properties according to Article 57(f) of REACH, Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

tetraethyl silicate

This substance is not considered to have endocrine-disrupting properties according to Article 57(f) of REACH, Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

## **SECTION 12: Ecological information**

Ecotoxicological information appears in this section when these data are available.

### 12.1 Toxicity:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

#### **Acute toxicity to fish**

Dust is harmful to aquatic organisms (LC50/EC50/IC50 are between 10 and 100 mg/L for the most sensitive species).

For similar substance(s)

LC50, Zebra fish (Danio/Brachydanio rerio), semi-static test, 96 h, > 100 mg/l, OECD Guideline 203 or Equivalent

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna, static test, 48 h, 39 mg/l, OECD Guideline 202 or Equivalent

#### **Acute toxicity to algae/ aquatic plants**

ErC50, Algae (Scenedesmus subspicatus), Growth rate, 72 h, Growth rate, 7.6 mg/l, OECD Guideline 201 or Equivalent

For similar substance(s)

NOEC, Algae (Scenedesmus subspicatus), Growth rate, 72 h, Growth rate, 1.1 mg/l, OECD Guideline 201 or Equivalent

#### **Toxicity to bacteria**

For similar substance(s)

EC50, Bacteria, 3 h, Respiratory rate, 14 mg/l

tetraethyl silicate

#### **Acute toxicity to fish**

Material is not classified as hazardous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 are greater than 100 mg/L for the most sensitive species).

LC50, zebrafish (Brachydanio rerio), 96 h, > 245 mg/l, Directive 67/548/EEC, Annex V, C.1.

#### **Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (large water flea), 48 h, > 75 mg/l, OECD test guideline 202

#### **Acute toxicity to algae/ aquatic plants**

ErC50, Pseudokirchneriella subcapitata (green algae), 72 h, Growth inhibition, > 100 mg/l, OECD test guideline 201

NOEC, Pseudokirchneriella subcapitata (green algae), 72 h, Growth inhibition, > 100 mg/l, OECD test guideline 201

#### **Toxicity to bacteria**

EC50, activated sludge, 3 h, Respiratory rate, > 100 mg/l, OECD test guideline 209

### 12.2 Persistence and Degradability:

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

**Biodegradability:** For similar substance(s) The material is expected to be very slowly degradable in the environment.

Does not pass OECD / EEC tests for biodegradability.

For similar substance(s) Time interval per 10 days : unsuccessful

**Biodegradation:** 3 %

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page14 of 17  
Print date: 17-2-2025

**Exposure time:** 28 d

**Method:** OECD Directive 301F or equivalent  
tetraethyl silicate

**Biodegradability:** The material biodegrades easily.

Passes OECD test(s) for rapid biodegradability.

**Time interval per 10 days:**

**Biodegradation:** 98 %

**Exposure time:** 28 d

**Method:** OECD Directive 301A or equivalent

Stability in water (half-life)

Hydrolysis, DT50, 4.4 h, pH 7, Half-life temperature 25 °C, OECD test guideline 111

**12.3 Bioaccumulation:**

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

**Bioaccumulation:** No relevant data found.

tetraethyl silicate

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or log Pow between 3 and 5).

**Partition coefficient:** n-octanol/water (log Pow): 3,18 EU Method A.8 (partition coefficient)

**12.4 Mobility in soil:**

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

No relevant data found.

tetraethyl silicate

No relevant data found.

**12.5 Results of PBT and vPvB assessment:**

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

tetraethyl silicate

This substance is not considered persistent, bioaccumulative nor toxic (PBT).

This substance is considered neither very persistent nor very bioaccumulative (vPvB).

**12.6 Endocrine disrupting properties**

The substance/mixture does not contain any components believed to have endocrine-disrupting properties according to REACH article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at level 0.1% or higher.

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

This substance is not considered to have endocrine-disrupting properties according to Article 57(f) of REACH, Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

tetraethyl silicate

This substance is not considered to have endocrine-disrupting properties according to Article 57(f) of REACH, Commission Regulation (EU) 2018/605 or Commission Delegated Regulation (EU) 2017/2100.

**12.7 Other Harmful Effects:**

Stannane, dimethylbis[(1-oxoneodecyl)oxy]-

This substance is not on the Montreal Protocol list of ozone-depleting substances.

tetraethyl silicate

This substance is not on the Montreal Protocol list of ozone-depleting substances.

## **SECTION 13: Disposal instructions**

**13.1 Waste treatment methods:**

Do not discharge into sewers, soil or surface water.

This product, when disposed of in its unused and uncontaminated state, must be treated as hazardous waste according to EC Directive 2008/98/EC.

Disposal practices must comply with all national and provincial laws and any municipal or local bylaws on hazardous waste.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page15 of 17  
Print date: 17-2-2025

Additional assessments may be required for used, contaminated and residual material.  
The assignment of an appropriate EWC waste group as well as an EWC waste code specific to this product depends on the application for which this product has been used.  
Consultation with waste management service.

## **SECTION 14: Information relating to transport**

Transport according to ADR rules for road transport, RID rules for railways, ADN for inland waterways, IMDG for sea and ICAO / IATA for air transport.

Country: Road transport: ADR, Rail transport: RID.

Transport documentation: waybill and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: bill of lading

Air: Air transport: ICAO / IATA.

Transport document: airway bill.

### **14.1 UN number**

UN no: UN1292

### **14.2 Proper cargo name according to UN model regulations**

Description :

ADR: UN 1292, FLAMMABLE LIQUID, N.O.S. (Tetraethyl Silicate)

IMDG: UN 1292, FLAMMABLE LIQUID, N.O.S. (TETRAETHYL SILICATE)

ICAO/IATA: UN 1292, FLAMMABLE LIQUID, N.O.S. (TETRAETHYL SILICATE)

### **14.3 Transport hazard class(es)**

ADR 3

IMDG: 3

ICAO/IATA: 3

### **14.4 Packing group**

ADR: III

IMDG: III

ICAO:IATA: III

### **14.5 Environmental hazards**

Marine pollution: No

### **14.6 Special precautions for the user**

ADR/RID: Hazard identification number: 30.

IMO/IMDG: EMS: F-E, S-E

IATA/ICAO: No data available.

### **14.7 Transport in bulk in accordance with Annex II to MARPOL 73/78 and the IBC Code**

The product is not transported in bulk.

This information is not intended to disclose all specific legislation, operational requirements/information about this product.

Additional information on transport can be obtained from a sales representative, or from customer service.

It is the responsibility of the transport company to comply with all legal provisions relating to the transport of goods.

## **SECTION 15: Statutory information**

### **15.1 Safety, health and environmental regulations and legislation specific to the substance or mixture:**

#### **REACH Regulation (EC) No 1907/2006**

This product contains components that are registered, exempt from registration, considered to be registered or not subject to registration as regulated by Regulation (EC) No 1907/2006 (REACH).

The aforementioned indications of REACH registration status are provided to the best of our knowledge and are assumed to be accurate as of the date shown above.

However, express or implied warranties are given.

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page16 of 17  
Print date: 17-2-2025

It is the responsibility of the buyer/user to ensure that his/her understanding of the regulatory status of this product is correct.

**REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII):**

Restriction conditions for the following dates should be considered:

Number on the list 3

Bis [(2-ethyl-2,5-dimethylhexanoyl) oxy] (dimethyl) stannane: (Number on the list 20)

Methanol: (Number on the list 69)

**Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.**

Regulation details: FLAMMABLE LIQUIDES

Number in Regulation: P5c

5 000 t

50 000 t

Indicated in regulation: ENVIRONMENTAL DATA

Number in regulation: E2

200 t

500 t

**Further information**

Take into account Directive 94/33/EC on the protection of young people at work or stricter national legislation, if applicable.

15.2 Chemical safety assessment:

No chemical safety assessment has been carried out for this substance/mixture.

**SECTION 16: Other information**

H226:	Flammable liquid and vapour.
H302:	Harmful if swallowed.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H319:	Causes severe eye irritation.
H332:	Harmful by inhalation.
H335:	May cause respiratory tract irritation.
H412:	Harmful to aquatic organisms with long-lasting effects.

**Classification and procedure are used to derive the classification for mixtures from Directive (EC) No 1272/2008**

Flam. Liq. - 3 - H226 - Based on product data or assessment

Skin Irrit. - 2 - H315 - Calculation method

Acute Tox. - 4 - H332 Method of calculation.

STOT SE - 3 - H335 Method of calculation.

**Revision**

Amendments made to sections 2.2, 2.3, 3.2, 8.1, 8.2, 9.1, 11.1, 12.1, 15

**Edge lettering**

2006/15/EC: Indicative occupational exposure limit values

2017/164/EU: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values

ACGIH: USA. ACGIH Threshold Limit Values (TLV).

ACGIH BEI: ACGIH - Biological Exposure Indices (BEI).

BE OEL: Occupational exposure limits

Dow IHG: Dow IHG

STEL: Short-term exposure limit

According to directive 1907/2006/EC, 2020/878  
Version 2.0 Revision date: 19-07-2022  
Trade name: Silicone ASSYST W22 - rapid hardener

Page: Page17 of 17  
Print date: 17-2-2025

TGG 15 min:	Short-time value
TGG 8 hr:	Limit value
TWA:	Time-weighted average
Acute Tox:	Acute toxicity
Aquatic Chronic:	(Chronic) Aquatic long-term hazard
Eye Irrit:	Eye irritation
Flam. Liq:	Flammable liquids
Skin Irrit:	Skin corrosion/irritation
Skin Sens:	Skin sensitisation
STOT SE:	Specific target organ toxicity - single exposure

## Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR Agreement); AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Association for the Testing of Materials; bw - Body Weight; CLP - Regulation on Classification, Labelling and Packaging; Regulation (EC) No 1272/2008; CMR - Carcinogenic, mutagenic or toxic to reproduction; DIN - Standard or the German Institute for Standardisation; DSL - List of substances used indoors (Canada); ECHA - European Chemicals Agency; EC-Number - EINECS number; ECx - Concentration associated with x% response; ELx - Charge capacity associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemicals (Japan); ErCx - Concentration associated with x% growth response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - IMO International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk; IC50 - Half-Maximum Inhibitory Concentration; ICAO - International Civil Aviation Organisation; IECS - Inventory List of Existing Chemicals in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korean Inventory of Existing Chemicals; LC50 - Lethal concentration for 50% of a test population; LD50 - Lethal dose for 50% of a test population (lethal dose median); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not otherwise specified; NO(A)EC - No discernible (negative) effect on concentration; NO(A)EL - No discernible (negative) effect on Level; NOELR - No discernible effect on cargo capacity; NZIoC - New Zealand inventory of chemicals; OECD - Organisation for Economic Co-operation and Development OECD; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, bioaccumulative and toxic substance; PICCS - Philippine inventory of chemicals and chemical substances; (Q)SAR - (Quantitative) structure-activity relationships; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH); RID - Regulations concerning the International Carriage of Dangerous Goods by Rail (RID); SADT - Self-accelerating decomposition temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwanese Chemicals Inventory List; TRGS - Technical Regulation on Hazardous Substances; TSCA - Toxic Substances Control Act (USA); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

We ask any customer or recipient of this Safety Data Sheet (MSDS) to read it carefully and, if necessary, to consult appropriate experts to understand the information contained in this MSDS and to be aware of the hazards posed by the product. The information in this document is given in good faith and is believed to be correct at the date of creation of this document. However, no express or implied warranty is given. Legal provisions may change and they may be different depending on the country. It is the buyer/user's responsibility to ensure that their activities comply with all local legal provisions. The information in this document relates only to the product as shipped. Since the conditions under which the product is used cannot be controlled by the manufacturer, the buyer/user must determine the conditions under which the product can be used in complete safety. Due to the proliferation of information sources, such as Safety Data Sheets (MSDS) from various manufacturers, we are not and cannot be responsible for MSDS obtained from other sources. If you have received a Safety Data Sheet from another source, or if you are not sure that you are in possession of the latest version of a Safety Data Sheet, please contact us.