



ASSYST sprl / A.S.O.W. sprl
Hellegatstraat 13a - 2590 Berlaar - Belgium
Tel: +32 495 50 61 14 / +32 496 83 70 27
Website: www.assyst.org / www.artsuppliesonweb.com
Email: ao@assyst.org / vera.opsommer@assyst.org

BONE GLUE

TYPE OF PRODUCTS:

Glue in beads based on protein from animal bones (cattle or similar).

APPLICATION AREAS:

Product with particularly suitable performance for industry: chemicals, wood, paper processing and metallurgy.

TECHNICAL CHARACTERISTICS

Views:

Brownish, solid in the form of pearls

For a standard solution 50% dry and 50% water variable +/- according to the different areas of application and needs.

Gelatinising ability:

approx. 130 bloom

Features:

- ✓ Proportional average open time.
- ✓ product preferably at a processing temperature of between 65-80°C to obtain the maximum curing capability.

RECOMMENDED CONDITIONS OF USE:

- ✓ The preparation of the product involves dissolving it in cold water. When the water has been fully absorbed, it is dissolved and heated au bain-marie until the operating temperature is reached. After this procedure, the product is ready for use. Do not mix with other products to avoid problems; the bone glue is only compatible with other glues of organic origin.
- ✓ It is recommended not to exceed the temperature of 90-100 ° C, as well as a temperature lower than the recommended temperature, because the adhesive's bonding values will be compromised.

Remark:

The above dilution ratios are indicative and can be varied according to the materials to be glued, the ambient temperature and humidity as well as the application conditions.

CLEANING:

The glue pot and the other parts of the machine can be cleaned with hot water.

STORAGE:

Up to 12 months from the date of delivery. Store in a cool and dry place. Ensure proper rotation of stocks.

SAFETY RULES:

Users should be made aware of the rules in the relevant safety data sheet before using or handling this product.