



ASSYST bvba / A.S.O.W. bvba
Hellegatstraat 13a - 2590 Berlaar - Belgium
Tel: +32 495 50 61 14 / +32 496 83 70 27
Website: www.assyst.org / www.artsuppliesonweb.com
Email: ao@assyst.org / vera.opsommer@assyst.org

GLASS FLEECE 30 GR/M²

DESCRIPTION:

Surface fleece M524-ECR30S consists of Advantex® 13 µm glass fibres. The glass fibre veil is bound by a modified styrene resin that is rapidly soluble in styrene resin systems. Designed to be used as a surface fabric for GRP laminates.

PRODUCT BENEFITS:

- ✓ Good surface appearance.
- ✓ Rapid solubility of styrene.

PHYSICAL ATTRIBUTES:

Feature	Test Method	Specification	Normal constraints	
			Min.	max.
Surface weight (g/m ²)	PTS-L-002	31.5	34.5	28.5
Binder content (%)	PTS-L-003	11	12.5	9.5
Thickness (mm)	PTS-L-007	0.33	0.36	0.3
Air permeability (l/m ² /s)	PTS-L-029	6300	6950	5650
Tensile strength Longitudinal (N/50mm)	PTS-L-015	-	-	20
Tensile strength across (N/50mm)	PTS-L-015	-	-	11